



LOCTITE[®] 7100[™]

October 2007

PRODUCT DESCRIPTION

LOCTITE[®] 7100[™] provides the following product characteristics:

Technology	Aqueous Based
Chemical Type	Mixture of surfactants
Appearance	Colorless
Odor	Odorless
Cure	Not applicable
Application	Leak Detector
Dispense Method	Spray
Propellant	Nitrogen

LOCTITE[®] 7100[™] is a product in an easy to use aerosol, that allows easy detection of suspected leaks. This product starts producing bubbles at areas where a leak is present. Non-toxic and non-flammable. LOCTITE[®] 7100[™] is designed for tracing leaks in all pressurized gas systems, compressed air, helium, nitrogen etc. as well as in iron, copper and plastic piping. This product is typically used in applications with an operating range of 10 °C to 50 °C.

TYPICAL PROPERTIES

Density @ 20 °C, g/ml	1
Viscosity, DIN CUP 4, seconds	10
pH	8.5
Surface Tension, ASTM D 1590, mN/m	27
Pressure @ 20 °C, Bar	8
Delivery Rate, g/s	3
Flash Point - See MSDS	

GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet (MSDS).

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials

Handling precautions

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on an open flame or any incandescent material.

Directions for use

1. Shake can thoroughly. Spray at a distance of about 15 to 20 cm onto the suspect area.
2. A leak will be clearly visible, as the product will start foaming at the leaking area. The product will continue to foam, allowing for a thorough search without rushing.

3. If the leak is not in the repair area, the leak search has to be extended to entire system. The leak will be in the area where the product starts foaming.
4. After the leak has been detected, wipe off excess product and perform appropriate maintenance.
5. To ensure the maintenance performed was successful, apply LOCTITE[®] 7100[™] again to the respective area.
6. On hydraulic components leaks are normally clearly visible without any product. However, for a leak check after repair or on new components, prior to component installation, LOCTITE[®] 7100[™] can be used for detecting potential leaks. For this purpose, fill the component with pressurised air and apply product to suspect area.

Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 2.0